

We claim:

1. A printable form comprising:
a first portion including a detachable wristband having an incorporated electronic identifier;
5 a second portion connected to the first portion and including a liner and detachable labels mounted on the liner.
2. The printable form of claim 1 further comprising perforations defining the detachable wristband.
- 10 3. The printable form of claim 1 wherein the electronic identifier is a radio frequency identification circuit.
4. The printable form of claim 3 wherein the electronic identifier is a
15 readable and writable circuit.
5. The printable form of claim 3 wherein the first portion includes a first printable layer and a second reinforcing layer of material.
- 20 6. The printable form of claim 5 further comprising a coating located on the first printable layer.
7. The printable form of claim 5 wherein the electronic identifier is positioned between the first printable layer and the second reinforcing layer.
- 25 8. The printable form of claim 1 wherein the wristband includes adhesive positioned to bond the wristband into a continuous band.
9. A printable form comprising:
30 a first layer having a detachable portion in the form of a wristband;
an electronic identifier incorporated into the wristband;
a second layer bonded to the first layer by an adhesive, said second layer having labels die cut therefrom; and
wherein the bond between the first layer and the die cut labels is a releaseable

bond allowing the labels and the adhesive contained thereon to be removed from the first layer.

10. The printable form of claim 9 further comprising an adhesive on the wristband, wherein the wristband includes two ends, and wherein the adhesive is located proximate to at least one end.

11. The printable form of claim 10 further comprising a release tab which is releasably bonded to the adhesive on the wristband end.

12. The printable form of claim 11 wherein the tab is additionally bonded to a portion of the first layer adjacent to the wristband such that when the wristband is removed the tab remains bonded to the first layer.

13. The printable form of claim 9 further comprising:
a reinforcing material permanently bonded to the first layer, wherein the first layer includes a first major surface and a second major surface;
wherein the second layer is bonded to the first layer on the first major surface, and the reinforcing material is bonded to the second major surface; and,
wherein the reinforcing material forms a part of the wristband and is arranged to provide strength to the detachable wristband both before and after removal from the form.

14. The printable form of claim 13 wherein the electronic identifier is an RFID tag.

15. The printable form of claim 13 further comprising an adhesive on the wristband, wherein the wristband includes two ends and wherein the adhesive is located proximate to at least one end on the reinforcing material.

16. The printable form of claim 15 further comprising a release tab which is releasably bonded to the adhesive on the wristband end.

17. The printable form of claim 16 wherein the tab is additionally bonded to

a portion of the first layer adjacent to the wristband such that when the wristband is removed the tab remains bonded to the first layer.

18. The printable form of claim 16 wherein the tab is additionally bonded to a portion of the reinforcing material which is bonded to the first layer adjacent to the wristband such that when the wristband is removed the tab remains bonded to the first layer.

19. The printable form of claim 9 further comprising a performance enhancing coating on at least one of the wristband and the labels.

20. A printable form comprising:
a first layer having a first and second major surfaces and a detachable portion in the form of a wristband;

an RFID tag incorporated into the wristband;
a second layer, bonded to the first major surface of the first layer by an adhesive, said second layer having labels die cut therefrom;

wherein the bond between the first layer and the labels is a releaseable bond allowing the labels and the adhesive contained thereon to be removed from the first layer;

a reinforcing material permanently bonded to the second major surface of the first layer; and,

wherein the reinforcing material forms a part of the wristband and is arranged to provide strength to the detachable wristband both before and after removal from the form.